



## Features

- Using environmental friendly refrigerant R134a or R1234yf
- Compact product line is a mono-block unit with a plug and play feature ensures immediately set up also with flange design for convenient through-wall or cabinet door mounting
- Closed loop cooling protects equipment from ambient environment, with adjustable indoor temperature set point from 20-40°C, ventilation not recommend any more since the system highest efficiency
- Adaptable for T3 condition which up to 55°C tropic area

Power supply	P/N	Model No.	Capacity	Dimension W/O flanges (mm)	Product Feature
230VAC	732010	AIYB-006-000-010	600W	546*315*175	CE
	732011	AIYB-006-000-011	600W		CE
	732020	AIYB-010-000-020	1000W		CE
	732021	AIYB-010-000-021	1000W		CE
	732030	AIYB-020-000-030	2000W		CE
	732031	AIYB-015-000-031	1500W		CE
	732032	AIYB-020-000-032	2000W	745*445*200	CE
	732033	AIYB-015-000-033	1500W		CE
	732120	AIYB-020-000-120	2000W		UL
	732121	AIYB-015-000-121	1500W	UL	
	732122	AIYB-025-000-122	2500W	UL	
	732040	AIYB-030-000-040	3000W	1150*485*225	CE
	732050	AIYB-050-000-050	5000W	1300*600*300	/
	732051	AIYB-040-000-051	4000W		/
	732110	AIYC-075-000-110	7000W		1400*650*400
	732311	AIYC-060-000-311	6000W	1150*485*435	/